

Eaton EVMIF116A

Catalog Number: EVMIF116A

Eaton Metered Input G4 Rack PDU, 0U, 22.5U, IEC-60309 input, 3m cord, 1ph, 3.7kW, 16A, 200-240V, 24 outlets (12)C13, (12)C39

General Specifications



Product Name	Catalog Number
Eaton Rack PDU G4	EVMIF116A
EAN	UPC
3553340697241	786689801380
Product Length/Depth	Product Height
1000 mm	53 mm
Product Width	Product Weight
52 mm	2.4 kg
Warranty	Compliances
3 year	CB
	LVD Directive
	RoHS Directive
	WEEE Directive
	Packaging Directive
	EMC Directive
Certifications	Model Code
IEC 62368-1	PDU G4 MI 0U 309 16A 1P
EN IEC 63000	12xC13,12xC39
CE	
EAC	
UKCA	
Cm	
Ukr	
IEC/EN 61000-6-2	
IEC/EN 61000-6-4	
EN 61000-3-2	
EN 61000-3-3	
CISPR 35/EN 55035	

Special features

Remote Site Management
Versatile C39 outlet
supports C14 or C20 power cord plug
High retention outlets designed to securely fit standard power cords and support P-Lock power cords
Cybersecurity standards UL 2900-1 and IEC 62443-4-2
Hot-Swap network control module
Network Cascading, connect up to 32 PDUs via network loop
Power sharing between two network modules PDUs ensures constant access to PDU data & sensors
1% IEC Class 1 billing grade measurement accuracy
Gigabit network card with 2x Gb ports
Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS
Optional sensor
Temperature/Humidity

Type

Metered input Rack PDU

Form factor

0U (Vertical)

Outlet control

No

Accessories

Rack PDU
Rack mounting accessories
Quickstart guide
Safety Instructions

Operating Temperature

Brochures

[Rack PDU G4 Brochure EN](#)

Declarations of conformity

[EU declaration of conformity Rack PDU G4](#)

0° to 60°C (32° to 140°F)

Mounting direction

Vertical

Color

Black

Material

Aluminium

Input connection

IEC-60309 16A 1Ph

Cord length

3m

Wattage

3.7 kW max

Amperage Rating

16A

Input voltage

200-240V

Phase

Single-phase

Frequency rating

50/60 Hz

Outlets

(12) C13, (12) C39

Number of Outputs C13

12

Number of Outputs C19

12

Number of outputs (other)

12

Number of outlets with earth pin

24

SNMP

Yes

Ethernet interface

Yes

Serial interface

Yes

Mass configuration

Yes

Electrical connection

Connecting cord with plug

Evaluation

At distance

Mounting Dimension (metrical)

52

Mounting dimension (standardized)

Metric

Switchable

No

Over voltage category

2

Series

G4



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)