

Jarretières Duplex LCUPC/LCUPC 2mm OS2 G657A1 2.00 MM Short boot

DCA_APL1L1DA12Yxxxx

Spécifications

- Connecteur A : **LC/UPC**
- Connecteur B : **LC/UPC**
- Simplex/Duplex : **Duplex**
- Monomode/Multimode : **Monomode**
- Type de fibre : **G657A1**
- Couleur de gaine : **Jaune**
- Diamètre de la gaine : **2mm**



Caractéristiques	
IL Max	≤ 0.30dB
IL Typ	≤ 0.20 dB
Return Loss	≥ 55/60 dB
Température de fonctionnement	-20°C - +70°C

Références	Désignations
DCA_APL1L1DA12Y0-5	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=0,5m
DCA_APL1L1DA12YLS2	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=2m
DCA_APL1L1DA12Y3	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=3m
DCA_APL1L1DA12Y5	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=5m
DCA_APL1L1DA12YLS10	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=10m
DCA_APL1L1DA12YLS15	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=15m
DCA_APL1L1DA12YLS20	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=20m
DCA_APL1L1DA12YLS25	Jarretière Duplex LCUPC/LCUPC 2mm OS2 G657A1 LSZH monomode short boot - L=25m